Technische Documentatie DOUBLE FRED (388046)

2. APPLIANCE TESTED

The specifications for the tested appliance are as follows:

•	ns for the tested appliance are as follows:		
Manufacturer:	Euromac B.V.		
Model:	FRED25/15 Art.nr.388046		
Serial number:	N		
Electrical data	Rated voltage	100-240	V
	Rated frequency	50/60	Hz
	Rated input current	2,5	Α
	Defrosting power	N	W
	Rated energy consumption	185	kWh/yea
Rated Volumes	Total volume	38	L
	Volume of fresh food/ "2-star" frozen food storage compartment (L)	N/38	L
Rated freezing capacity		N	kg/24h
Climate class		SN/N/ST/T	
Refrigerant		R134a	
Compartment type		2-star frozen food	
How many external doors does it have?		2	
Frost-free or not.		Not	
Defrost controller type (variable, run-time, fixed time, other).		N	
Condenser type (grill (stack)/skin (smooth wall)/fan forced (including direction of the exhaust)/other, as applicable).		Fan forced	
Condenser location (back/side/underneath, as applicable).		Underneath	
Features (convenience feature/automatic ice maker/ through the door ice and/or water dispenser/ other).		N	
Compressor details: single speed, variable speed, multiple compressors.		Variable speed	
For variable defrost controls, min and max defrost interval (where known)		N	
Ambient controlled anti- condensation heater (with, without).		Without	
For user controlled anti-condensation heaters, describe the switch and any associated controls.		N	
Is the appliance a built-in product?		No	

5. ENERGY CONSUMPTION TEST

Energy consumption tests were measured in accordance with EN 62552-1:2020, EN 62552-2:2020, EN 62552-3:2020, EU 2017/1369, EU 2019/2016, EU 2019/2019, (EU) 2021/340 and (EU) 2021/341.

Test method

The temperatures in the fresh food compartment were measured at three locations using the copper or brass cylinders. The temperatures in frozen storage compartment were measured at five locations using the copper or brass cylinders.

For no defrost control cyle or where stability is established for a period between defrosts (Case SS1), after steady state have been attained, the test period shall consist of three blocks and each block of test data shall be equal in length consisting of n temperature control cycles, adjacent and not less than 4 h in duration. The temperature Tss1-i of each compartment i and the average power Pss1 is determined as the average of all measured values included in the time period covered by Blocks A, B and C.

For steady state determined between defrosts (Case SS2), data shall be used between the start of two defrost and recovery periods to calculate the steady state power. The methods of calculating Pss2 and Tss2-i refer to Fomula 12 and 13.

Requirements

When the steady state is attained, Case SS1 or SS2 acceptance criteria shall be met. The temperature of fresh food compartment shall be at or below 4°C. The temperature of three-star and four-star compartment shall be at or below -18°C. The temperature of two-star compartment shall be at or below -12°C.

Test conditions			
Ambient temperature:		16 °C	32 °C
Power supply:		230 V 50 Hz	230 V 50 Hz
Temperature control settings:		ECO L:-12, R:-12/ ECO L:-9, R:-11	MAX L:-14, R:-14
Steday state power, Pss(W)		13,861/11,952	25,208
Steady state Temperature, T _{ss} (℃)	Fresh food compartment	N	N
	"2-star"Frozen food compartment L	-14,0/-11,4	-12,2

т		1	•
	"2-star"Frozen food compartment R	-12,5/-11,6	-12,0
	cellar compartment	N	N
Defrost and recovery Energy consumption, ΔE _{df} (W · h)		N	N
Defrost Interval	, $\Delta t_{df}(h)$	N	N
Temperature change during defrost and recovery, ΔTh _{df} (K · h)	Fresh food compartment	N	N
	"2-star"Frozen food compartment L	N	N
	"2-star"Frozen food compartment R	N	N
	cellar storage compartment	N	N
Average temperature, T _{average}	Fresh food compartment	N	N
	"2-star"Frozen food compartment L	N	N
	"2-star"Frozen food compartment R	N	N
	cellar storage compartment	N	N
Energy consumption E ₁₆ and E ₃₂ (kWh/24hrs)		0,307	0,605
Daily energy consumption, E _{daily} (kWh/24hrs)		0,456	

Test requirements and results

Item	Rated	Measured	Deviation
Overall dimensions (width × depth × height, mm)	695×400×455	695×400×455	
Space required in use (width × depth × height, mm)	745×450×505	745×450×505	
Overall space required in use (width × depth × height, mm)	745×450×905	745×450×905	
Fresh food storage compartment(L)	N	N	N
"2-star" frozen food storage compartment(L)	38	38,0	0
Total volume (L)	38	38,0	0

DETAILS OF ENERGY EFFICIENCY GRADE CALCULATIONS

Parameters	Rated value	Measured value	
Climate class:	SN/N/ST/T		
Volume V _c (L)	V fresh food compartment: N	V fresh food compartment:N	
	V _{2-star frozen food compartment} :38	V 2-star frozen food compartment: 38,0	
- n is the number of compartments	1		
Total volume V (L)	38	38	
	For fresh food compartment: N		
Thermodynamic parameter r _c	For "2-star" frozen food compartment:1,80		
Modeling parameter N _c	For fresh food compartment: N		
The second personal second	For "2-star" frozen food comp	partment:138	
Modeling parameter M _c	For fresh food compartment: N		
	For "2-star" frozen food comp	partment:0,15	
Defeation A	For fresh food compartment:	N	
Defrost factor A _c	For "2-star" frozen food compartment: 1,00		
	For fresh food compartment: N		
Built-in factor B _c	For "2-star" frozen food compartment: 1,00		
Combi parameter C	1,00	1,00	
Door heat loss factor D	1,00		
Standard annual energy consumption SAE (kWh/a)	148,26	148,26	
$SAE = C \times D \times \sum_{c=1}^{n} A_c \times B_c \times [V_c/V] \times (N_c + V \times r_c \times M_c)$			
E ₁₆ (Energy consumption at 16°C) (kWh/24h)	1	0,307	
E ₃₂ (Energy consumption at 32°C) (kWh/24h)	0,605	0,605	
E ₂₅ (Energy consumption at 25°C) (kWh/24h)	N	N	
Daily energy consumption			
E _{daily} (kWh/24h)	0,456	0,456	
$E_{daily} = 0.5 \times (E_{16} + E_{32})$,	5, 700	
For low noise refrigerating appliance	N	N	
$E_{daily} = E_{25}$			

Auxiliary energy	0	0	
E _{aux} (kWh/a)			
Load factor L	0,9		
Annual energy consumption			
AE (kWh/a)	185	184,93	
$AE = 365 \times E_{daily}/L + E_{aux}$			
EEI (%)	404.0	404.7	
EEI = AE/SAE.	124,8	124,7	
Energy efficiency classes*	F	F	
EEI limits for E*	100% < EEI ≤ 125%		
EEI limits for minimum energy	EEI ≤ 125%		
performance requirements**			
If following the EEI limits or not**	Pass	Pass	

Remark*: the energy efficiency class is determined according to table 1 of ANNEX II of COMMISSION DELEGATED REGULATION (EU) 2019/2016 and (EU) 2021/340;

Remark**: From 1 March 2021, the maximum EEI for refrigerating appliances is determined according to table 1 of ANNEX II of COMMISSION REGULATION (EU) 2019/2019 and (EU) 2021/341.